

## CT-K Series

1-800-345-7873 www.cuzn.com

CT-101, CT-2K, CT-3K Systems Available in Chrome or White.

## **Installation**

- 1) Unscrew aerator from kitchen faucet.
- 2) Replace the aerator with the countertop filter's diverter valve. Hand tighten. (if the diverter valve does not fit try using one of the enclosed diverter adapters.
- 3) To activate filtration system, turn on cold water. While water is running, pull out stem on diverter valve. Allow water to run for five minutes or until water runs clear. This removes harmless carbon dust from the filter.
- 4) To stop water flow to the filtration system, turn off your faucet and the stem will return to the original position.

## Refilling your CT system

- 1) All cartridges come with a donut shaped gasket on one side.
- 2) The gasket should point toward the smaller of the two housing parts which screw together.
- 3) For double canister system the specialty cartridge (eg. Fluoride) is always first in line. (on the inlet side) The standard KR cartridge is always last in line. (on the exit side)
- 4) For double and triple systems the exit side is where the spout is or the side with the silver label.
- 5) An enclosed filter wrench will help unscrewing and reassembling your unit. Remember not to over tighten and check that the O-ring is in the proper position.

## **Limited Warranty**

This CuZn filter is designed for use on potable systems only. Its effectiveness may be reduced in areas where municipally treated water has chemicals such as poly phosphates to alleviate water problems caused by high iron content. Do not use this filter in water supplies that may reach pressures over the recommended use state on the instructions. The manufacturer warrants this product to be free from defects in materials and workmanship when installed, operated, and maintained in the manner instructed, for a period of one year from date of purchase. The warranty is limited to the repair or replacement of any filter that fails to perform due to faulty materials or workmanship during the warranty period. To qualify for this warranty, the filter must be maintained and replaced as stated in the instructions. Save your receipt. CuZn is not responsible for any damages occurring during the misuse of this product.



Step 1





Step 2





Capacity:

KR-101N: 10,000 gallons Cartridges will last approximately 1 year AR-1, 2000 gallons at 50 ppb NR-1, FR-1, CR-1 Cartridges will last approximately 1 year RN-1 Cartridge will last approximately 6 months or up to 1000 gallons. Warranty: 5 years pro-rated on housing,

Maximum Temperature 85 F
Maximum Pressure 125 psi
Maximum Flow 2 gpm

1 year on cartridge

