Instructions for ALL Under Counter Non-rechargeable Units UC-200, UC-200F, UC-285, UC-50

- 1) SHUT OFF COLD WATER SUPPLY
- 2) Place CuZn™ Water Filtration System under counter.

 Note location of inlet and outlet holes (Inlet at the bottom and outlet at the top of the unit).
- 3) Disconnect the cold water supply tube from shut-off valve. (Leave the connection to the faucet in place.)
- 4) Carefully bend that existing tube and connect it to the outlet (top fitting) of your new CuZn Filter.
- 5) Connect the 3/8" flexible stainless tubing (included in our package) from the inlet (bottom fitting) of your CuZn filter to the water supply at the shut off valve.
- 6) Turn on water supply. Check for leaks.
- 7) Connections should be tightened securely but not overtightened. If leaks persist, turn water supply back off, disconnect, and apply sealant to leaking joint. Not all piping arrangements are the same. If supplied parts are not enough to make the appropriate connections, obtain what is needed at a local hardware or plumbing supply store.
- 8) Turn cold water on and run at least five minutes or until water is clear, to remove any media dust or carbon fines. Drink in good health!

Stay informed!
Ask your local water supplier
what is in your water and let
CuZn help you make it healthier!
We have units designed for
removing Chlorine, Chloramines
Fluoride and many more including
custom units. Contact your
distributor or a CuZn rep with
any questions.



Outlet. Use existing line to connect to faucet.

Maximum Temperature 85 F
Maximum Pressure 125 psi
Maximum Flow 2 gpm

Inlet. Connect to water supply

Limited Warranty

This CuZn filter is designed for use on potable systems only. Its effectiveness may be reduced in areas where municipally treated water has chemicals such as polyphosphates to alleviate water problems caused by high iron content. Do not use this filter in water supplies that may reach pressures over the recomended use stated on the instructions. The manufacturer warrants this product to be free from defects in materials and workmanship when installed, operated, and maintained in the manner instructed, for a period of one year from date of purchase. The warranty is limited to the repair or replacement of any filter that fails to perform due to faulty materials or workmanship during the warranty period. To qualify for this warranty, the filter must be maintained and replaced as stated in the instructions. Save your receipt. CuZn is not responsible for any damages occurring during the misuse of this product.

